



BY BOUNDLESS TECHNOLOGIES

ADD S 3153 Video Display Terminal



The ADDS 3153 display terminals provide advance data access, data manipulation and display features not found in ordinary terminals. Dual-host functionality allows users to simultaneously access applications from multiple hosts. Cut and paste capability saves time by allowing user to move data from one application to another and from host to host without lengthy keystroke sequences or retyping.

By offering a broad range of screen formats and keyboard programmability, the ADDS 3153 provides the flexibility to meet each users specific requirements.

The 3153 emulation set includes the IBM 3151, Wyse WY-50/50+, WY-60, DEC VT-100, VT-220, VT 320 and the ADDS Viewpoint and TeleVideo TVI-925. The ADDS 3153 is an ideal solution for customers using IBM display terminals in legacy applications.

Boundless Technologies 1-800-231-5445



BY BOUNDLESS TECHNOLOGIES

ADD5 3153 Video Display Terminal

Display Features:

- ◇ 14" Flat face, reduced glare, high resolution screen
- ◇ Bezel to Bezel overscan
- ◇ 60, 71, 82 and 100 hz selectable refresh rates for clear flicker free viewing
- ◇ Choice of Green, Amber or White phosphor
- ◇ 24,25,28,42,43 or 50 lines with top and/or bottom status lines
- ◇ 80 or 132 columns
- ◇ 10 pages of memory
- ◇ Variable-speed smooth scroll
- ◇ Double high, double wide characters
- ◇ Selectable screen saver

Desk Accessories:

- ◇ Calculator
- ◇ Calendar
- ◇ Clock
- ◇ ASCII Chart

Communications:

- ◇ Full/half duplex
- ◇ Local block
- ◇ Monitor mode
- ◇ Serial host Port
 - RS-232C main host
 - DTE, DB 25 female
 - up to 134.4k baud
- ◇ Serial Auxiliary Port
 - RS-232C second host/aux serial port
 - DCE, DB 25 female
 - Up to 38.4k baud
- ◇ Parallel Printer Port
 - IBM PC and Centronic compatible
- ◇ Optional Ethernet
 - 10BaseT TCP/IP
- ◇ Optional current loop
- Dual Host Support**
- ◇ Simultaneous connection and operation with two hosts
- ◇ Flexible display formats
- ◇ "Hot key" to alternate between hosts
- ◇ Printer port support for both hosts

Terminal Emulations:

- ◇ IBM 3151
- ◇ ADD5 Viewpoint
- ◇ VT 100
- ◇ VT 220
- ◇ VT 320
- ◇ Wyse 50
- ◇ Wyse 50+
- ◇ Wyse 60
- ◇ TVI 925
- ◇ SCO Console
- ◇ BBS ANSI
- ◇ AT 386

Regulatory Agencies:

- ◇ UL
- ◇ TUV-GS Mark
- ◇ CSA 22.2., cUL
- ◇ CE
- ◇ MRP-II
- ◇ DHHS
- ◇ VCCI
- ◇ EPA Energy Star
- ◇ ISO 92413
- ◇ VCCI
- ◇ EN 55022 Class B
- ◇ VFG 243 B

Power:

- ◇ 90-264 Vac, 47-63 hz
- ◇ .20-.50a (max) operating
- ◇ EPA Energy Star ® "Sleep Mode"

Physical Characteristics

- ◇ L: 13.0", 33 cm
- ◇ W: 12.5", 31.8 cm
- ◇ H: 13.4", 34 cm
- ◇ Shipping weight: 29 lbs.

Boundless Technologies

1916 Route 96

Phelps, NY 14532

Phone (toll-free): 1-800-231-5445

Phone: 1-315-548-6189

Fax: 1-315-548-5100

www.boundless.com