

ADD S

BY BOUNDLESS TECHNOLOGIES

VT525 Video Display Terminal

Designed by DEC and built by Boundless - more than 6 million VT terminals are installed worldwide

4 independent color sessions and split-screen viewing

Use any SVGA monitor (not included)



With its color and multi-session text capabilities, the VT525 provides four full color, independent sessions. Each session offers 16 colors from a 4,096-color palette. The use of color text allows users to highlight crucial information in applications.

The VT525 is an ideal replacement for customers currently using WYSE 325 terminals. In addition to the WYSE 325 the emulation set includes the DEC VT100, VT220, VT320, VT420, Dorio 10/20, Wyse WY-50/50+/55, WY-60, WY-150, ADDS A2 and TeleVideo 910+, 925 and 950.

The VT525 supports ANSI color protocol, ASCII color emulation, and color support for monochrome monitors. Monochrome applications can have instant color! The flexible and reliable VT525 can be used with any SVGA monitor.

Built in the Boundless "JIT" manufacturing facility in western NY allows rapid delivery of The VT525 to any location in the world. Boundless backs all its VT terminals with a money back guarantee and a 3 year warranty.

Our focus on providing custom desktop solutions to our customers has made Boundless the client choice of every major server manufacturer for the last 30 years.

Boundless Technologies 1-800-231-5445



BY BOUNDLESS TECHNOLOGIES

VT525 Video Display Terminal

Display Features:

- ◇ Monitor—any SVGA
- ◇ Controls up front
- ◇ 24,25,26,36,42,48,50, 53 lines
- ◇ 80 or 132 columns*
- ◇ 8 pages of memory
- ◇ Windows like set up
- ◇ Double high, double wide characters
- ◇ Selectable screen saver
- ◇ Programable tab stops
- ◇ Hot key access to the Desktop features

Desk Accessories:

- ◇ Calculator
- ◇ Calendar
- ◇ Clock
- ◇ Character Set

Communications:

- ◇ Full/half duplex
- ◇ Block
- ◇ Serial host Port
 - RS-232C main host
 - DTE, DB 25 male or female
- ◇ Two DEC RS-423 6-pin MMJ
- ◇ Parallel Printer Port
 - IBM PC and Centronic compatible printer port (female)
- ◇ Flow Control
 - DTR/DSR
 - XON/XOFF,XPC, or none
- ◇ Baud Rate—300 to 115.2K Baud

Keyboards

- ◇ ALL keys programmable to 8 levels by user or host to UDK, function or alpha-numeric

Terminal Emulations:

- ◇ ADDS Viewpoint
- ◇ VT 100
- ◇ VT 220
- ◇ VT 320
- ◇ Dorio 10
- ◇ Wyse 50/50+
- ◇ Wyse 55
- ◇ Wyse 60/160
- ◇ Wyse 120/150
- ◇ TVI 910+
- ◇ TVI 925/950
- ◇ SCO Console

Regulatory Agencies:

- ◇ cUL
- ◇ TUV
- ◇ FCC-B,
- ◇ CE
- ◇ MRP-II
- ◇ DHHS
- ◇ VCCI
- ◇ EPA Energy Star
- ◇ ISO 92413

Power:

- ◇ 100-240 Vac, 47-63 hz

* LCD displays supported in 80-column mode only

Boundless Technologies
1916 Route 96
Phelps, NY 14532
Phone (toll-free): 1-800-231-5445
Phone: 1-315-548-6189
Fax: 1-315-548-5100
www.boundless.com

Boundless, ADDS and the Boundless logo are all trademarks of the Boundless Technologies Inc. All other trademarks and registered trademarks are the property of their respective owners. These specifications are subject to change at any time.